cont

detecting means for detecting a voltage level of a signal line connected to a personal computer;

power supply control means for controlling a supply of an electric power from a power source to a predetermined circuit in accordance with an output of said detecting means;

discriminating means for discriminating whether or not a communication request of a predetermined procedure has been received from the personal computer after the electric power of the power source was supplied to the predetermined circuit by said power supply control means, wherein said discriminating means detects the voltage level of the signal line connected to the personal computer and is powered by the personal computer via the signal line; and

control means for continuing the supply of the electric power from the power [supply] source once said discriminating means discriminates a presence of the communication request.

(Amended) An apparatus according to claim 1, wherein said detecting means detects a logic level of a data line arranged between the personal computer and said peripheral apparatus and said [communication request] discriminating means detects the presence or absence of the communication request at the logic level detected by said detecting means.

con (

3. (Amended) An apparatus according to claim 2, wherein the data line and a <u>power supply</u> line [for the power supply] are separately provided.

5. (Amended) An apparatus according to Claim 4, wherein said discriminating means determined whether or not the electronic camera has been operated by an operator or controlled by the personal computer, and said control means executes a control in accordance with a result of the [judgment] discrimination.

6. (Amended) An apparatus according to claim 2, wherein said detecting means and discriminating means use the [signal] logic level transmitted through the data line as [a] the power source.

50825 7. (Amended) A camera which can be connected to a computer apparatus, comprising:

recording means for recording a photographed image;

detecting means for detecting a level of a data

line which is connected to a personal computer;

discriminating means for judging whether or not an input signal is a predetermined command from the personal computer, wherein said discriminating means detects the voltage level of the data line connected to the personal the Same data line computer and is powered by the personal computer via the data line;

cont B2 image output means for outputting image data recorded by said recording means to the personal computer; and

control means for starting a supply of an electric power to said recording means and said image output means according to a detection result of said detecting means, and then controlling the supply of the electric power according to a discrimination result of said discriminating means so as to continue the supply of the electric power once the predetermined command is discriminated by said discriminating means, and to stop in the case where the predetermined command is not discriminated by said discriminating means.

8. (Amended) A camera according to Claim 7, wherein [said detecting means detects] the level detected by said detecting means is a logic level of the data line arranged between the personal computer and said camera and said discriminating means detects the presence or absence of a communication request at the logic level detected by said detecting means.

Bz

11. (Amended) A camera according to claim 7, wherein said detecting means and said discriminating means use the [signal] level transmitted through the data line as a power source.

REMARKS